

CRUISEMASTER

DO45

4.5 TONNE ALL-TERRAIN COUPLING

PLUS | TAME THE BEAST




INSTALLATION • MAINTENANCE • WARRANTY • ACCESSORIES

CRUISEMASTER.COM.AU

   @CRUISEMASTERCOUNTRY

PRODUCT FEATURES



FOR USE IN AUSTRALIA -
ADR RATED TO 4500kg (9920lb)
D-VALUE 24.5kN V-VALUE 14.5kN

FOR USE IN NORTH AMERICA -
SAE J684 RATED TO CLASS 4 TRAILERS

Applicable Patents:
2011101337, 2006207859, 2011253645

LEGEND

1. High Visibility Reflective Reversing Strip
2. Impact Resistant Bumper
3. Locking Slide Plate
4. Lock Button *Push Down to Release Lock Plate*
5. Pin Locating Port
6. Tow Pin Shaft (1-1/4" UNF AU)
7. Gen.2 Check-Lock Dust Cap
8. Spindle Bushes
9. Mounting Bolts
10. Grease Nipple
11. Support Webbing
12. Slotted Nut & Pin
13. Handbrake Mount
14. Handbrake Cable Mounting Holes
15. Limiting Roll Pin *Can be removed for increased clearance*
16. Padlock Hole
17. Yoke Pivot Bolt *Only to be adjusted by a Cruisemaster approved repairer*
18. Universal *Full Universal Assembly includes Bumper & Locking Assembly*


INSTALLATION

Mounting the D045^{Plus} Tow Pin onto the Tow Bar

IMPORTANT: V1 D045 PIN IS NOT COMPATIBLE WITH THE D045^{PLUS}

Fit tow pin to towbar using spring washer and 1-1/4" UNF nut supplied and torque to 750Nm (553lbs.ft).


It may be necessary to hold the tow pin in place using the supplied c-spanner.



Bolting the D045^{Plus} Coupling onto the Drawbar


Always use four new bolts to secure Coupling to Trailer. Bolt grades to be minimum M14 Class 8.8 torqued to 140Nm (104lbs.ft) or 5/16" Grade 5 bolts torqued to 150Nm (110lbs.ft). Use either nylon insert nuts or spring washers. **DO NOT ATTEMPT TO WELD** the coupling to the drawbar. **The coupling must always be mounted flat on the drawbar plate.**

A drawbar weight of at least 50kg (110lb) and not exceeding 450kg (992lb) is recommended.



= Coupling Mounting Surface (Flat)

= Drawbar Mounting Surface (Flat)



Use of Weight Distribution Hitches

The D045^{Plus} can be used with load distribution hitches providing the coupling movement is not obstructed and the maximum downward load of 450kg (992lb) prior to tightening of bars is not exceeded. With a WDH adaptor attached to the vehicle, clearance should also be checked to ensure the trailer drawbar does not foul, particularly in tight reversing situations.

HITCHING UP WITH THE D045^{PLUS}

Note: This process is now universal between D035 and D045^{Plus} models

STEP 1

Ensure the Tow Pin Cover is removed from Tow Pin.

Step 2

The Tow Pin and Universal should be free of sand, dirt and foreign objects. Lightly greased to ensure premature wear is avoided.

Step 3

Set the coupling to the unlocked position. Do so by pushing down on the Red Lock Button while simultaneously pushing back the Locking slide plate towards the Red Lock Button. When in position the Lock Button will spring back and pressure will be removed from the Locking Plate. At this stage in the unlocked position the viewing port in the centre of the locking mechanism should be clear.

Step 4

Raise height of trailer so the coupling is above the vehicle Tow Pin height by adjusting Jockey Wheel or Stand.

Step 5

Align Coupling over Tow Pin by moving either vehicle or trailer, then lower coupling onto tow pin using Jockey Wheel or Stand. Ensure that the Universal is fully seated on the Tow Pin; the Tow Pin will protrude through locking plate as visible via the view port.


Step 6

Once in position Push the same Red Lock Button used in Step 3 to reset the locking plate into the locked position. The Locking Plate will slide forward into place simultaneously to the button push.


Step 7

Secure the Checklock Cap, the cap will emit an audible snap when secured correctly.


For video instructions visit
[http://cruisemaster.com.au/
videos](http://cruisemaster.com.au/videos) or search on YouTube
"Cruisemaster - Hitching Up
with the D035"



UNLOCKED:
- Locking plate protruding at rear
- Pin Locating Port clear



LOCKED:
- Engage lock with Red Lock Button
- Locking plate protruding at front
- Pin protruding through Locating Port



If you are not confident in fitting this product yourself, contact Cruisemaster to find your closest preferred service agent.

Final stage of hitching up will look as per above.

SAFETY

- Keep hands and fingers clear of coupling when attaching.
- Ensure trailer safety chains are attached whilst coupling or uncoupling.
- Do not use Tow Pin or Coupling for recovery purposes.

HANDBRAKE

If you have a coupling with a part number ending in "-I" this indicates the model includes an "Integrated" Handbrake.

Part numbers ending in "-R" indicates the Handbrake is "Removed".

Some drawbar designs will restrict the handbrake on an integrated model, in this situation we recommend the use of a Cruisemaster remotely mounted handbrake or side mount handbrake.


Handbrake Part Numbers

Std Remote Mount Handbrake - 56A-HB

Side Mount Handbrake - 56A-HB-S/M

V3/PLUS Handbrake Attachment - 56A-HB-V3

Available from www.cruisemaster.com.au



MAINTENANCE

To ensure a long service life we recommend the following periodic maintenance procedures.

Keep the Tow Pin and Universal mating surfaces clean and lightly greased at all times.

Check the condition of Tow Pin O-Ring and replace if necessary (O-RING NITRILE BS213 (15/16" x 1-3/16" x 1/8")).

Regularly lubricate grease points with multi-purpose lithium grease.


Periodic adjustment of the Slotted Nut & Pin may be required if coupling 'Yoke' loosens in the housing excessively, to be completed by a competent person.

Flush with clean water or air hose if locking mechanism does not open fully due to dirt ingress.

** Cruisemaster recommends a thorough maintenance check is conducted every 10,000 Km or 12 months.*

** Please note while the DO45^{Plus} Zn-Ni with E-Coat finish provides superior corrosion protection it may fade with extended exposure to UV. This does not affect the operation of the DO45^{Plus}. To best maintain the finish of the product, we recommend covering the DO45^{Plus} coupling when not in use if stored outside and exposed to direct UV.*

Available Replacement Parts



For a complete list of spare components visit cruisemaster.com.au/shop.

ACCESSORIES

Looking to set up a second vehicle to tow with your D045^{Plus}, looking for a D045^{Plus} enhancement or simply replacing a misplaced item?

There is a full range of supported accessories for the D045^{Plus}.

Tow Pin Kit (Incl. Pin / Cover / Tool) - 18D-D045-TP-AU-KIT

Pin Cover - 50M-4029

Universal C-Spanner - 50K-133

- * D045 V1 accessories and spares **are not** compatible with the D045^{Plus} model.
- * D035 accessories and spares **are not** compatible with the D045^{Plus} model.

CRUISEMASTER BI-LOCK (COUPLING LOCK)

Keep your investment safe and secure with the Cruisemaster Bi-Lock.
NEW D045 SPECIFIC BI-LOCK!

Step 1

Insert machined pin into the top of the coupling and engage the locking mechanism.

Step 2

Fit the lock chamber to the pin end underneath the coupling and lock with key.

Step 3

Cover the key hole with supplied rubber dust cover to protect the locks chamber.



* D035 model Bi-Lock will also fit the D045^{Plus} but will allow excess movement of the locking pin

For a complete list of spare components visit cruisemaster.com.au/shop.



GEEBUNG, BRISBANE 07 3624 3822 CRUISEMASTERTPC.COM.AU

FULL WEIGHT ASSESSMENTS

4X4 FITOUTS & ACCESSORIES

CARAVAN SERVICING

UNDERBODY RETROFITS & REPAIRS

THE EXPERTS IN THE COMPLETE TOWING EXPERIENCE!



CRUISEMASTER.COM.AU/NATIONAL-SERVICE-NETWORK/

APPROVED SERVICE AGENTS

NATION WIDE!

Cruisemaster™ has a proud history of engineering and real life testing, these elements have meant Cruisemaster™ is the trusted leader in the industry when it comes to products being designed to last. Our confidence to stand behind our product gives you the confidence it will get you there and back again.

This product comes standard with a 3 year warranty. A complimentary 2 year warranty extension is available for this product.

Visit the Cruisemaster website for a full list of Terms & Conditions.

To Claim the full 5 years of warranty register this product online;

www.cruisemaster.com.au/warranty-policy/

